

# TW-6

## PIPE & CABLE LOCATOR



The Model TW-6 "Two-Box" metal detector finds underground pipes, cables, manhole covers, vaults, valve boxes and other metallic objects.

The TW-6 is used primarily by water departments, telephone companies, power companies, gas companies and petroleum pipeline companies when making repairs and rearranging lines. The TW-6 shows where to dig, as well as where NOT to dig.

To increase the instrument's sensitivity, Fisher engineers removed all unnecessary metallic parts on the TW-6, replacing them with durable ABS molded plastic. Coil windings are designed with completely upgraded electronics and nonmetallic parts have boosted the tracing distance of the TW-6.

In the Fisher tradition, the TW-6 is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.



### Features

- Crystal controlled frequency in both transmitter and receiver increases tracing distance
- Unlike other units that use a separate transmitter and receiver, the TW-6 when mounted on the handle, can conduct "blind" searches of an area to locate an underground pipe or cable when the starting point is unknown.
- VCO (Voltage Controlled Oscillator) gives a wider range of audio signal to indicate the presence of metal. Even after the meter pegs, the audio signal goes much higher in pitch and volume.
- Noise cancelling circuitry eliminates power line interference.
- Powered by 16 standard AA (penlight) batteries: eight in the transmitter and eight in the receiver.
- Weighs only 5 1/2 pounds.



200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 [www.fisherlab.com](http://www.fisherlab.com) [info@fisherlab.com](mailto:info@fisherlab.com)

Fisher Labs has been serving the demanding needs of the utility industry with innovative locating solutions - Since 1931. From pipe & cable locators, valve & box locators, sound & leak detectors to water level indicators, Find it... with Fisher!

# TW-6 specifications



Specifications subject to change without notice.

## **T**ransmitter

Operating Frequency.....81.92 kHz + .005%  
Batteries.....8 each. AA (NEDA 15)  
Weight.....2 1/2 lbs. (1.1 kg)  
Dimensions.....11 1/2" x 9" x 3" (29 x 23 x 7.6 cm)  
Operating Temperature.....-10°F to +120°, (-23°C to +48°C)

## **R**eceiver

Operating Frequency.....81.92 kHz + .005%  
Batteries.....8 each. AA (NEDA 15)  
Weight.....3 lbs. (1.36 kg)  
Sensitivity.....Normal: 400 uV typical.....High: 8 uV typical  
Signal-to-noise Ratio.....110 dB  
Headset Impedance.....600 ohms (mono).....8 ohms (stereo)  
Dimensions.....11 1/2" x 9" x 3" (29 x 23 x 7.6 cm)  
Operating Temperature.....-10°F to +120°, (-23°C to +48°C) depending on batteries used

Total Weight.....5 1/2 lbs. (2.5 kg) - (without handle of accessories, ground plate assembly & op manual.)  
Total Shipping Weight.....6 3/4 lbs. (3 kg) - (including only ground plate assembly and operating manual.)  
Total Shipping Volume.....69 cu. ft. (19.5 liters)

## **A**ccessories

### Optional Equipment:

Tracer Probe	SR-81 Sonde
Coupling Clamp	Stereo Headphones
3 pc Handle Kit	Fisher Phones
Hard Carrying Case	Nicad Recharge Battery System
	Ground Rod Harness Assembly

## 2-Year Warranty

Fisher warrants the TW-6 to be free of defects in materials and workmanship when it is shipped from the factory. The terms of this warranty are fully explained in a warranty registration card that accompanies the instrument. Complete factory and field service facilities support the warranty.

\*Warranty may vary outside the U.S. See your distributor for details.

## Ordering Information

### US & Canadian Customers Contact:

#### FISHER LABS

200 W. Willmott Rd., Los Banos, CA 93635-5501  
T 209.826.3292 F 209.826.0416 info@fisherlab.com  
www.fisherlab.com

### All Other Countries Contact:

#### Fisher Export Department

282 State Street, North Haven, CT 06473 USA,  
T 203.288.1638 F 203.287.8099  
email: fisher@exportdept.com

