

**PRECISION**

# HUMIDITY/TEMP./DEW POINT METER

**Model : HT-3009**

**ISO-9001, CE, IEC1010**



## FEATURES

- \* The best professional hygrometer.
- \* Humidity + Temperature + Dew point are combined into one meter.
- \* 0.01 %RH humidity resolution.
- \* 0.01 degree temperature resolution.
- \* Very fast humidity measuring response time.
- \* 2 %RH humidity accuracy.
- \* Dew point measurement.
- \* Manual and auto data logger.
- \* Data logger function with flexible sampling time selection, can save max. 1000 reading data with recall.
- \* Records Max. and Min. readings.
- \* Auto shut off saves battery life.
- \* Data hold.
- \* RS 232 PC serial interface.
- \* Separate humidity & temp. probe, easy operation. & remote measurement.



**Lutron**

**LUTRON ELECTRONIC**

***The Art of Measurement***

## PRECISION HUMIDITY + TEMP. + DEW POINT METER

### Model : HT-3009

FEATURES	
<ul style="list-style-type: none"> <li>* The best hygrometer in the world.</li> <li>* Humidity + Temperature + Dew point are combined into one meter, intelligent and professional.</li> <li>* 0.01 %RH resolution for the humidity reading, 0.01 degree resolution for the humidity reading.</li> <li>* Very fast humidity measuring response time.</li> <li>* 2 %RH humidity accuracy, high precision.</li> <li>* Dew point measurement.</li> <li>* Manual and auto data logger.</li> <li>* Data logger function with flexible sampling time selection, can save max. 1000 reading data with recall.</li> <li>* Just few panel buttons, easy operation.</li> <li>* Microprocessor circuit assures maximum possible accuracy, provides special functions and features.</li> </ul>	<ul style="list-style-type: none"> <li>* Large LCD with two display, easy readout.</li> <li>* Heavy duty &amp; compact housing case, designed for easy carry out &amp; operation.</li> <li>* Records Maximum and Minimum readings with Recall.</li> <li>* Auto shut off saves battery life.</li> <li>* Data hold function for freezing the desired value on display.</li> <li>* RS 232 PC serial interface.</li> <li>* Show the humidity &amp; temperature values on the LCD display at same time.</li> <li>* Built-in low battery indicator.</li> <li>* Wide humidity &amp; temp. measuring range.</li> <li>* Separate humidity &amp; temp. probe, easy operation. &amp; remote measurement.</li> </ul>

GENERAL SPECIFICATIONS			
Circuit	Custom one-chip of microprocessor LSI circuit.	Data Output	RS 232 PC serial interface.
Display	59 mm x 34 mm, 16 mm ( 0.63" ) digit size. dual function LCD display,	Operating	Meter : 0 to 50 °C.
		Temperature	Probe : 0 to 60 °C.
Measurement Unit	Humidity : %RH ( Relative Humidity )	Operating Humidity	Main Instrument : Less than 80% R.H.
	Temperature : °C or °F.	Humidity	Probe : 0 to 100 %RH.
	Dew point : °C or °F.	Power Supply	006P DC 9V battery ( Alkaline or Heavy duty type ).
Response Time	Less than 4 seconds.	Power Current	Approx. DC 4.6 mA.
	@ Reach the 85% reading value	Weight	313 g/0.69 LB. @ Battery is not included.
Temperature Compensation	Automatic temp. compensation for the humidity function.	Dimension	Main instrument : 203 x 76 x 38 mm ( 8.0 x 3.0 x 1.5 inch ). Humidity Sensor Probe : 197 mm ( 7.8 inch ) in length.
Sampling Time of Data Logger	Manual	Accessories Included	Instruction manual.....1 PC. Humidity probe.....1 PC. Carrying case.....1 PC.
	Auto		
Data Hold	Freeze the display reading by push button.	Optional Accessories	RS232 cable, UPCB-02 USB cable, USB-01 Data Acquisitio software, SW-U801-WIN Data Logger software, SW-DL2005
Memory Recall	Maximum & Minimum value.		
Sampling Time	Approx. 0.8 second.		
Power off	Auto shut off saves battery life or manual off by push button.		

ELECTRICAL SPECIFICATIONS		
<b>Humidity/ Temperature</b>		
Humidity	Range	0 % to 100 % R.H.
	Resolution	0.01 % R.H.
	Accuracy	± 2% R.H. @ 20 %RH to 80 %RH @ 10 °C to 40 °C
Temperature	Range	0 °C to 50 °C, 32 °F to 122 °F.
	Resolution	0.01 degree
	Accuracy	°C - ± 0.5 °C. @ 5 °C to 35 °C.
<b>Dew Point</b>		
°C	Range	-25.3 °C to 48.9 °C
	Resolution	0.01 °C
°F	Range	-13.5 °F to 120.1 °F.
	Resolution	0.01 °F.

\* Appearance and specifications listed in this brochure are subject to change without notice.

0703-HT3009