



CE

2803 IN



CE

2804 IN

FEATURES

- Microprocessor controlled with advanced safety features.
- Displays and sound warning if external voltage is present.
- Battery life extended by Enersave™ feature.
- Continuous battery monitoring.
- Auto-ranging/auto-off.
- Built-in carrying case, test leads in separate pouch.
- Real-time bargraph display of test voltage and voltage decay during discharge.
- Audible and visual message displayed if external voltage is present.
- Large LCD.
- Display can be customized for special orders.
- Show test time duration (up to 99.9s) for easy comparison.
- EEPROM calibration.
- IEC 1010-1 CAT.III

SPECIFICATIONS

Model	2803 IN				2804 IN			
Test Voltage (DC V)	0.5KV	1KV	2.5KV	5KV	1KV	2.5KV	5KV	10KV
Measuring Ranges (Auto-Ranges)	0-25GΩ	0-50GΩ	0-125GΩ	0-250GΩ	0-50GΩ	0-125GΩ	0-250GΩ	0-500GΩ
Accuracy	0-50GΩ :±3% of reading 50-250GΩ :±5% of reading				0-50GΩ : ± 3% of reading 50-500GΩ :±5% of reading			
Dimensions	170(L)×120(W)×95(D)mm				170(L)×120(W)×95(D)mm			
Weight (Battery Included)	930g Approx.				1030g Approx.			
Power Source	1.5V (AA)×8 Batteries				1.5V (AA)×8 Batteries			
Accessories	Test leads (see page 38) Shoulder belt Instruction manual Batteries				Test leads (see page 38) Shoulder belt Instruction manual Batteries			