

## HOTSTICKS AND CUTTERS

### SWITCH HEAD STICK

- Switch heads are made of bronze
- Designed to NEMA standards

FT	1 1/4" DIAMETER		1 1/2" DIAMETER	
	CAT NO	LBS	CAT NO	LBS
4	460-4	1.5	-----	-----
6	460-6	2.3	462-6	2.8
8	460-8	3.0	462-8	3.6
10	460-10	3.2	462-10	4.8
12	460-12	3.5	462-12	6.5
14	-----	-----	462-14	7.3
16	-----	-----	462-16	8.2
18	-----	-----	462-18	9.1
20	-----	-----	462-20	10.0

### DISCONNECT HEAD STICK

- Heavy duty
- For large switches and disconnects

FT	1 1/4" DIAMETER		1 1/2" DIAMETER	
	CAT NO	LBS	CAT NO	LBS
4	461-4	1.6	-----	-----
6	461-6	2.4	541-6	3.1
8	461-8	3.6	541-8	3.7
10	461-10	4.8	541-10	4.9
12	461-12	6.5	541-12	6.6
14	-----	-----	541-14	7.4
16	-----	-----	541-16	8.3
18	-----	-----	541-18	9.2
20	-----	-----	541-20	10.1

### UNIVERSAL HEAD STICK

- Can adapt with any universal tool found in the Hotstick Accessories Section

FT	1 1/4" DIAMETER		1 1/2" DIAMETER	
	CAT NO	LBS	CAT NO	LBS
4	567-4	1.4	-----	-----
6	567-6	1.7	-----	-----
8	567-8	2.6	-----	-----
10	567-10	3.3	469-10	4.5
12	567-12	4.0	469-12	6.5
14	-----	-----	469-14	7.3
16	-----	-----	469-16	8.3
18	-----	-----	469-18	9.2
20	-----	-----	469-20	10.1

### INSULATED HEAD STICK

- For confined spaces and tight switch gear
- Prong is made of solid fiberglass material

FT	1 1/4" DIAMETER		1 1/2" DIAMETER	
	CAT NO	LBS	CAT NO	LBS
4	501-4	1.2	-----	-----
6	501-6	2.1	502-6	2.3
8	501-8	2.6	502-8	3.1
10	501-10	3.5	502-10	4.3
12	501-12	4.3	502-12	5.2
14	-----	-----	502-14	6.2
16	-----	-----	502-16	7.1
18	-----	-----	502-18	8.1



567-4



460-4



461-4



501-4